


IE340 Series

Industrial Ethernet Layer 3 Switches

The IE340 Series of Industrial Ethernet Layer 3 switches provide network infrastructure to digitally transform industry.



Overview

Allied Telesis IE340 Series switches are the perfect solution for access connectivity in industrial automation and control networks.

Their low latency, high availability and high capacity enables seamless integration with industrial applications, supporting multiple transmission streams. They are hardened to withstand difficult environmental conditions, such as electromagnetic noise, wide-ranging temperatures, high humidity, and vibration.

The IE340 Series provides network infrastructure for many vertical markets and related applications, such as:

- ▶ **Building automation**
Facility management including security and access control, fire protection, energy management, heating/ventilation/air-conditioning, and lighting control.
- ▶ **Cranes & Logistics**
Control of automated stacker cranes and other devices that boost the efficiency of dynamic warehouse environments.
- ▶ **Industrial automation and process control**
Interconnection of machines, IoT devices, sensors, and more. Instant communication between systems and people enables improved efficiency and resilience in manufacturing environments.
- ▶ **Marine control and monitoring**
Seamless communication for vessels such as ships, high speed light water craft, and offshore units.
- ▶ **Railway transportation signalling and telecommunications**
Control signaling and telecommunication for improved safety, risk management, operating efficiency, and signage.

- ▶ **Roadway transportation traffic control**

Adaptive traffic control, telematics, and preventive maintenance.

- ▶ **Smart cities**

Public space and urban infrastructure that provides safety and security, parking management, environmental metering, lighting, and information kiosks.

- ▶ **Wastewater treatment**

Industrial sewage treatment plants for efficient and reliable water purification. Control systems ensure process optimization by intelligent control, regulation, and monitoring.

IT/OT convergence

Improve productivity and decision-making by integrating your operational technology (OT) and information technology (IT). Use the intelligence of Industry 4.0 to collect, analysis, and manage all your data in real time.

Micro-segmentation security

Reduce the attack surface of your OT network and have granular control of device-to-device communications with micro-segmentation. The IE340 Series supports SDN-based micro-segmentation solutions for more security, maintainability, and visibility than traditional security models.

Network automation and orchestration

Powerful automation options include Allied Telesis Autonomous Management Framework™ Plus (AMF Plus), and an open standard-based northbound API.

For easy integration into complex networks comprising physical, virtual, and multi-vendor devices, the IE340 Series features:

- ▶ NETCONF/RESTCONF + YANG data modelling for network automation.
- ▶ OpenFlow v1.3 for Software Defined Networking (SDN) orchestration.

Key Features

- ▶ 100Mbps¹ / 1Gbps uplink ports
- ▶ EMC for industrial plants
- ▶ AlliedWare Plus™ operating system
- ▶ Allied Telesis Autonomous Management Framework™ Plus (AMF Plus)
- ▶ NETCONF/RESTCONF with YANG data modelling
- ▶ OpenFlow v1.3 for SDN
- ▶ QoS with traffic shaping
- ▶ Efficient forwarding of multicast streams
- ▶ Routing capabilities (BGP, ECMP, OSPF, RIP, and static)
- ▶ Extensive features for cybersecurity and denial of service prevention
- ▶ Active Fiber Monitoring™ (AFM)
- ▶ High Availability networking (EPSRing™, ITU-T G.8032, MRP)
- ▶ Automation and control protocols (Modbus/TCP, PROFINET IO)
- ▶ Upstream Forwarding Only (UFO)
- ▶ IEEE 802.3at PoE+ sourcing (up to 30W)
- ▶ 240W PoE power budget with dynamic allocation
- ▶ Continuous PoE
- ▶ Extended operating temp range: -40°C to 75°C (tested @85°C)¹
- ▶ Fanless design
- ▶ Graceful thermal shutdown
- ▶ Protection circuits
- ▶ Alarm monitoring with trigger facility
- ▶ Redundant power inputs

¹ Not supported on the IE340L model

Key Features

Network Automation

- ▶ AMF Plus is a suite of tools providing centralized control and network automation, as well as visual intent-based network management. It has the intelligence to set-up, optimize, and maintain the network according to predefined goals and policies.
- ▶ Powerful features like centralized management, auto backup, auto upgrade, auto provisioning and auto recovery enable plug-and-play networking and zero touch management.
- ▶ Integration with our Vista Manager visual monitoring and management platform means AMF Plus² also provides intent-based features like:
 - Health monitoring to easily investigate, analyze and improve overall network health.
 - Smart ACLs to control and secure the resources that clients use in the network.
 - Intent-based QoS to deal with network bandwidth contention.
- ▶ AMF Plus is scalable and can be either deployed integrated into Allied Telesis equipment, or on multi-tenant cloud architecture.

Northbound Interfaces

- ▶ Open standard-based interfaces are supported to easily integrate with modern management systems.
- ▶ NETCONF/RESTCONF with YANG data modeling provides a standardized way to represent data and securely configure devices.
- ▶ OpenFlow is a key technology for SDN orchestration. SDN controllers and other tools support automated behavior in a network, and allow customized applications and services to be run.

Micro-segmentation for Network Security

- ▶ Micro-segmentation enhances converged IT/OT network security by reducing the number of entry points for attackers or intruders. Isolating applications, data, and endpoints hampers the ability of intruders or malware to move within the network.
- ▶ SDN network orchestration enables self-learning Artificial Intelligence to propagate and adapt security policies to mitigate evolving cyber threats.

Resiliency

- ▶ EPSRing™ and ITU-T G.8032 ERPS enable a protected ring capable of recovery within as little as 50ms. These features are perfect for high performance and high availability.
- ▶ High-availability automation networks are supported with Media Redundancy Protocol (MRP) as defined by IEC62439-2. MRP used in ring networks allows up to 50 devices to have guaranteed and deterministic switchover behavior.

- ▶ Spanning Tree protocols RSTP and MSTP, along with static LAGs and the dynamic Link Aggregation Control Protocol (LACP), support high availability in star network topologies.

Automation and Control Protocols

- ▶ Automation and control protocols enable integration with OT supervisory and control systems.

PROFINET IO is a communication protocol for data exchange between I/O controllers, like SCADA and PLC, with I/O devices over Ethernet networks.

Supporting PROFINET certification, the IE340 Series has I/O device properties that provide diagnostic data.

They support these communication channels:

 - Standard TCP/IP (PROFINET NRT): suitable for non-deterministic functions such as parametrization, video/audio transmissions and data transfer to higher level IT systems.
 - Real Time (PROFINET RT): TCP/IP layers are bypassed in order to have deterministic performance for automation applications.
 - ▶ Modbus/TCP is intended for supervision and control of automation equipment. It is a variant of the MODBUS protocol using TCP/IP for communications on Ethernet networks.
- The IE340 Series supports read/write register access and heartbeat functionality for efficient process control of both SCADA and slave devices.

Precise Time Synchronization (IEEE 1588)

- Measurement and automation systems involving multiple devices often require accurate timing in order to facilitate event synchronization and data correlation. The IEEE 1588 Precise Time Protocol is a fault tolerant method enabling clock synchronization in a distributed system that communicates using an Ethernet network; this deterministic communication network is designed to provide precise timing for automation applications and measurement systems.
- ▶ The IE340 Series supports IEEE 1588 (PTPv2) as Transparent Clock, and perform an active role on Ethernet networks reducing the effects of Jitter.

Quality of Service (QoS)

- ▶ Comprehensive low-latency wire-speed QoS provides flow-based traffic management with full classification, prioritization, traffic shaping and min/max bandwidth profiles. Enjoy boosted network performance and guaranteed delivery of business-critical services and applications.

sFlow

- ▶ sFlow is an industry-standard technology for monitoring high-speed switched networks. It provides complete visibility into network use, enabling performance optimization, usage accounting/billing, and defense against security threats. Sampled packets sent to a collector ensure it always has a real-time view of network traffic.

Active Fiber Monitoring (AFM)

- ▶ Active Fiber Monitoring prevents eavesdropping on fiber communications by monitoring received optical power. If an intrusion is detected, the link can be automatically shut down, or an operator alert can be sent.

VLAN Mirroring (RSPAN)

- ▶ VLAN mirroring allows traffic from a port on a remote switch to be analyzed locally. Traffic being transmitted or received on the port is duplicated and sent across the network on a special VLAN.

VLAN Translation

- ▶ VLAN Translation allows traffic arriving on a VLAN to be mapped to a different VLAN on the outgoing paired interface.

VLAN Access Control List (ACLs)

- ▶ ACLs simplify access and traffic control across entire segments of the network. They can be applied to a VLAN as well as a specific port.

Upstream Forwarding Only (UFO)

- ▶ UFO lets you manage which ports in a VLAN can communicate with each other, and which only have upstream access to services, for secure multi-user deployment.

Dynamic Host Configuration Protocol (DHCP) Snooping

- ▶ DHCP servers allocate IP addresses to clients, and the switch keeps a record of addresses issued on each port. IP source guard checks against this DHCP snooping database to ensure only clients with specific IP and/or MAC address can access the network. DHCP snooping can be combined with other features, like dynamic ARP inspection, to increase security in Layer 2 switched environments, and also provides a traceable history, which meets the growing legal requirements placed on service providers.

² From AW+ 5.5.2-2 onwards, an AMF Plus license operating in the network provides all standard AMF network management and automation features, and also enables the AMF Plus intent-based networking features menu in Vista Manager EX (from version 3.10.1 onwards).

Key Features continued

Link Layer Discovery Protocol–Media Endpoint Discovery (LLDP–MED)

- ▶ LLDP-MED extends LLDP basic network endpoint discovery and management functions. LLDP-MED allows for media endpoint specific messages, providing detailed information on power equipment, network policy, location discovery (for Emergency Call Services) and inventory.

Power over Ethernet Plus (PoE+)

- ▶ With PoE, a separate power connection to media endpoints is not necessary. PoE+ reduces costs and gives even greater flexibility with up to 30W per port. This enables connecting high-power devices such as advanced security camera, kiosks, POS terminals, Wi-Fi access points, and LED light fixtures.
- ▶ You may configure the overall PoE power budget to match the real capabilities of the external Power Supply Unit (PSU). The PoE power budget may be allocated automatically and dynamically, based on the current usage of each powered device.
- ▶ If the devices connected to a switch require more power than the switch can deliver, the switch will deny power to some ports, according to the assigned priority.

Continuous PoE

- ▶ Continuous PoE allows the switch to be restarted without affecting the supply of power to connected devices. Smart lighting, security cameras, and other PoE devices will continue to operate during a software upgrade on the switch.

Port Based DHCP IP Address Assignment

- ▶ DHCP server port-based address allocation ensures a replacement device receives the same IP address - even though the client-identifier or client hardware address has changed.
- ▶ The supports Industrial Automation and Control Systems (IACS), which are very sensitive to operation outages. When devices such as sensors and actuators fail, they must be replaced immediately.

Assigning the same IP address to the replaced device allows the OT supervisory system to take control and resume operation as quickly as possible, minimizing downtime.

Alarm Monitoring and Trigger facility

- ▶ The IE340 Series alarm facility monitors the switch and responds to any problems. Example of alarm events include:
 - Main power supply failure
 - Over-temperature
 - Port link down
 - Alarm Input
 - System power budget exceeded
 - PoE device exceeds port power budget

- ▶ Triggers based on alarm events provide a smart mechanism that automatically changes the network configuration to reduce downtime.

Alarm Input/Output

- ▶ Alarm Input and Output responds to an event instantly and automatically with predefined actions. The 2-pin terminal blocks may be connected to sensors and actuator relays.
- ▶ Alarm Input receives signals from external devices like motion sensors and magnets that trigger specific actions when something changes.
- ▶ Alarm Output controls external devices like strobes and sirens when an event occurs.

Protection Circuits

- ▶ Optimized protection circuits guard against the following abnormal conditions:
 - Reverse input voltage polarity
 - Over- and under-voltage
 - Over-current, peak-current and short-circuit
 - Over-temperature

Enhanced Thermal Shutdown

- ▶ Enhanced thermal shutdown acts to restrict PoE power and services when the switch exceeds a safe operating temperature.
- ▶ The system restores operation when the temperature returns to acceptable levels.

- ▶ The redundant power inputs are for higher system reliability and to allow UPS emergency power over an extended period of time.

Dual power inputs

- ▶ The redundant power inputs are for higher system reliability and to allow UPS emergency power over an extended period of time.

Gigabit and Fast Ethernet SFP ports

- ▶ The IE340 Series SFP ports support both Gigabit and Fast Ethernet Small Form-Factor Pluggables (SFPs).

This supports phasing in Gigabit fiber switches over time, allowing connectivity to legacy 100FX devices in the meantime. Supporting both speeds of SFP allows organizations to stay within budget as they migrate to faster technologies.


- ▶ The IE340L supports Gigabit SFPs only.

Premium Software License

- ▶ By default, the IE340 Series offers a comprehensive feature set that includes static routing. The feature set can easily be upgraded with premium software licenses.



Key Solutions



*Coming soon

Media Redundancy Protocol (MRP), EPSRing and ERPS (ITU G.8032) provide high-speed resilient ring connectivity. This diagram shows how the IE Series can support a variety of ring network topologies.

The IE Series operates at a wide temperature range, and allows deployment in outdoor and harsh industrial environments.

PoE sourcing models support remotely controlled Pan, Tilt and Zoom (PTZ) video cameras, WiFi access points and more.

Management can be automated either with the Allied Telesis Autonomous Management Framework™ Plus (AMF Plus), or by 3rd party tools via the open standard northbound interface.

Specifications

PRODUCT	10/100/1000T (RJ-45) COPPER PORTS	100/1000X SFP PORTS	1000X SFP PORTS	TOTAL PORTS	POE ENABLED PORTS	SWITCHING FABRIC	FORWARDING RATE
IE340-12GP	8	4	-	12	8	24Gbps	17.8Mpps
IE340-12GT	8	4	-	12	-	24Gbps	17.8Mpps
IE340-20GP	16	4	-	20	16	40Gbps	29.7Mpps
IE340L-18GP	16	-	2	18	16	36Gbps	26.7Mpps

Performance

RAM memory	512MB DDR SDRAM
ROM memory	128MB flash
MAC address	16K entries
Packet Buffer	1.5 MBytes (12.2 Mbits)
Priority Queues	8
Simultaneous VLANs	4K
VLAN ID range	1–4094
Jumbo frames	9KB L2 jumbo frames
Multicast groups	511 (Layer 2), or 256 (Layer 2) and 256 (Layer 3) ³

Other Interfaces

Type	Serial console (UART)
Port no.	1
Connector	RJ-45 female
Type	USB2.0 (Host Controller Class)
Port no.	1 ⁶
Connector	Type A receptacle
Type	Alarm input (320µA @3.3Vdc)
Port no.	1
Connector	2-pin Terminal Block
Type	Alarm output (1A @30Vdc)
Port no.	1
Connector	2-pin Terminal Block

Flexibility and Compatibility

- ▶ SFP ports support any combination of Allied Telesis 100Mbps and 1Gbps SFP modules listed in this document under Ordering Information

Reliability

- ▶ Modular AlliedWare™ operating system
- ▶ Protection circuits against abnormal operations
- ▶ Redundant power input
- ▶ Full environmental monitoring of temperature and internal voltage levels
- ▶ Enhanced Thermal Shutdown

Industrial Automation

- ▶ IEEE 1588 PTP one-step variant
- ▶ IEEE 1588 PTP two-step variant⁴
- ▶ IEEE 1588 PTP End-to-End Transparent Clock
- ▶ IEEE 1588 PTP Peer-to-Peer Transparent Clock⁴
- ▶ IEEE 1588 PTP profile: Default
- ▶ Modbus/TCP with master/slave heartbeats facility
- ▶ PROFINET IO non-real-time and real-time (NRT/RT)

Management Features

- ▶ Allied Telesis Autonomous Management Framework™ Plus (AMF Plus) node
- ▶ NETCONF/RESTCONF northbound interface with YANG data modelling
- ▶ OpenFlow northbound interface
- ▶ Web-based Graphical User Interface (GUI)

³ When PIM is enabled.

⁴ Coming in a later firmware release. Contact Sales representative for availability

- ▶ Industry-standard CLI with context-sensitive help
- ▶ Powerful CLI scripting engine
- ▶ Built-in text editor
- ▶ Event-based triggers allow user-defined scripts to be executed upon selected system events
- ▶ Link Layer Discovery Protocol (LLDP)
- ▶ Link Layer Discovery Protocol - Media Endpoint Discovery (LLDP-MED)
- ▶ SNMPv1/v2c/v3 support
- ▶ Comprehensive SNMP MIB support for standard based device management
- ▶ Console management port on the front panel for ease of access
- ▶ Front panel LEDs provide at-a-glance PSU status, PoE status, and fault information
- ▶ Eco-friendly mode allows ports and LEDs to be disabled to save power
- ▶ USB interface allows software release files, configurations, and other files to be stored for backup and distribution to other devices
- ▶ Recessed Reset button
- ▶ Extensive remarking capabilities
- ▶ IP precedence and DiffServ marking based on Layer 2, 3 and 4 headers
- ▶ Limit bandwidth per port or per traffic class down to 64kbps
- ▶ Policy-based QoS and traffic shaping
- ▶ Policy-based QoS based on VLAN, port, MAC and general packet classifiers
- ▶ Policy-based storm protection
- ▶ Strict priority, weighted round robin or mixed scheduling
- ▶ Taildrop for queue congestion control
- ▶ Wirespeed traffic classification with low latency for real-time streaming media applications

IPv4 Features

- ▶ Black hole routing
- ▶ Directed broadcast forwarding
- ▶ Equal Cost Multi Path (ECMP) routing
- ▶ Dynamic routing (OSPF, RIP, and BGP)
- ▶ Static unicast and multicast routes for IPv4
- ▶ UDP broadcast helper (IP helper)

IPv6 Features

- ▶ Device management over IPv6 networks with SNMPv6, Telnetv6 and SSHv6
- ▶ IPv4 and IPv6 dual stack
- ▶ IPv6 hardware ACLs
- ▶ Dynamic routing (OSFPv3, RIPng, and BGP+)
- ▶ Static unicast routing for IPv6
- ▶ IPv6 Ready certified

Multicasting Features

- ▶ Internet Group Management Protocol (IGMPv1/v2/v3)
- ▶ IGMP snooping with fast leave
- ▶ IGMP query solicitation
- ▶ Multicast Listener Discovery (MLDv1/v2)
- ▶ MLDv2 for IPv6
- ▶ MLD snooping
- ▶ IGMP/MLD proxy (multicast forwarding)
- ▶ Protocol Independent Multicast - Dense Mode (PIM-DM)
- ▶ Protocol Independent Multicast - Sparse Mode (PIM-SM)

Quality of Service

- ▶ 8 priority queues with a hierarchy of high priority queues for real-time traffic, and mixed scheduling, for each switch port

Resiliency Features

- ▶ Control Plane Prioritization (CPP) ensures the CPU always has sufficient bandwidth to process network control traffic
- ▶ Dynamic link failover (host attach)
- ▶ Ethernet Protection Switching Ring (EPSR) with SuperLoop Prevention (EPSR-SLP)
- ▶ Ethernet Ring Protection Switching (ITU-T G.8032 ERPS)
- ▶ Link Aggregation Control Protocol (LACP)
- ▶ Loop detection and thrash limiting
- ▶ Media Redundancy Protocol (MRP)
- ▶ Multiple Spanning Tree Protocol (MSTP)
- ▶ PVST+ compatibility mode
- ▶ Rapid Spanning Tree Protocol (RSTP)
- ▶ Router Redundancy Protocol (RRP) snooping
- ▶ Spanning Tree Protocol (STP) root guard

Security Features

- ▶ Access Control Lists (ACLs) based on layer 3 and 4 headers
- ▶ Authentication, Authorization and Accounting (AAA)
- ▶ Auth-fail and guest VLANs
- ▶ Configurable ACLs for management traffic
- ▶ BPDU protection
- ▶ DHCP snooping, IP source guard and Dynamic ARP Inspection (DAI)
- ▶ DoS attack blocking and virus throttling
- ▶ Dynamic VLAN assignment
- ▶ HTTP over TLS (HTTPS)
- ▶ MAC address filtering and MAC address lockdown
- ▶ Network Access and Control (NAC) features manage endpoint security
- ▶ Password protected bootloader
- ▶ Port-based learn limits (intrusion detection)
- ▶ Private VLANs and port isolation for multiple customers using the same VLAN
- ▶ RADIUS local server (100 users) and accounting
- ▶ Secure Copy (SCP)
- ▶ Strong password security and encryption
- ▶ TACACS+ authentication and accounting

- ▶ Tri-authentication: MAC-based, web-based and IEEE 802.1X

Virtual LAN Features

- ▶ Generic VLAN Registration Protocol (GVRP)
- ▶ VLAN stacking, Q-in-Q
- ▶ VLAN translation
- ▶ Upstream Forwarding Only (UFO)

Services

- ▶ Domain Name System (DNS) relay
- ▶ DNSv6 relay
- ▶ Dynamic Host Configuration Protocol (DHCP) server and relay
- ▶ DHCPv6 server and relay
- ▶ HyperText Transfer Protocol (HTTP/1.1)
- ▶ Network Time Protocol (NTP) for IPv4 and IPv6
- ▶ Simple Mail Transfer Protocol (SMTP)
- ▶ Secure Shell (SSHv2/v3)
- ▶ TELNET
- ▶ Trivial File Transfer Protocol (TFTP)

Diagnostic Tools

- ▶ Active Fiber Monitoring (AFM) detects tampering on optical links
- ▶ Automatic link flap detection and port shutdown
- ▶ Built-In Self-Test (BIST)
- ▶ Cable fault locator (TDR)
- ▶ Connectivity Fault Management (CFM), Continuity Check Protocol (CCP) for use with ITU-T G.8032 ERPS
- ▶ Event logging via Syslog over IPv4
- ▶ Find-me device locator
- ▶ Optical Digital Diagnostic Monitoring (DDM)
- ▶ Ping polling for IPv4 and IPv6
- ▶ Port and VLAN mirroring (RSPAN)
- ▶ sFlow
- ▶ TraceRoute for IPv4 and IPv6
- ▶ UniDirectional Link Detection (UDLD)

Environmental Specifications

- ▶ Operating temperature range:⁵
 - IE340 model: -40°C to 75°C (-40°F to 167°F)⁶
 - IE340L model: -40°C to 65°C (-40°F to 149°F)
- ▶ Storage temperature range: -40°C to 85°C (-40°F to 185°F)
- ▶ Operating humidity range: 5% to 95% non-condensing
- ▶ Storage humidity range: 5% to 95% non-condensing
- ▶ Operating altitude: 3,000 meters maximum (9,843 ft)

Mechanical

- ▶ EN 50022, EN 60715 standardized mounting on rails

Warranty

- ▶ Five-year limited hardware warranty. Refer to the Term & Policies page on the Allied Telesis web site.

COMPLIANCE	IE340	IE340L
Compliance Mark	CE, FCC, ICES, IPv6 Ready, RCM, TEC ⁸ , UKCA, UL, VCCI	
Hazardous Substances Compliance	RoHS, China-RoHS, JGSSI, REACH, SCIP, TSCA, WEEE	
Safety ⁷	AS/NZS 62368-1 CAN/CSA C22.2 No.60950-22 CAN/CSA C22.2 No.61010-1 CAN/CSA C22.2 No.62368-1 EN/IEC/UL 60950-22 EN/IEC/UL 61010-1 EN/IEC/UL 61010-2-201 EN/IEC/UL 62368-1	CAN/CSA C22.2 No.60950-22 CAN/CSA C22.2 No.62368-1 EN/IEC/UL 60950-22 EN/IEC/UL 62368-1
Electromagnetic Immunity	EN 55035 EN 61000-6-2	
Harmonic current emission	EN/IEC 61000-3-2 ⁷	
Voltage fluctuation and flicker	EN/IEC 61000-3-3 ⁷	
Electrostatic discharge (ESD)	EN/IEC 61000-4-2, level 3	
Radiated susceptibility (RS)	EN/IEC 61000-4-3, level 3, level x (20V/m)	
Electrical fast transient (EFT)	EN/IEC 61000-4-4,	Signal port: level 4 DC power port: level 3 Earth port: level 2
Lighting/surge immunity (Surge)	EN/IEC 61000-4-5, installation class 3 for outdoor Signal port: level 3 (L-E) DC power port: level 3 (L-E, R-E), level 2 (L-L)	
Conducted immunity (CS)	EN/IEC 61000-4-6, level 3	
Magnetic field	EN/IEC 61000-4-8, level 4	
AC voltage dips and interruption	EN/IEC 61000-4-11 ⁷	
DC voltage dips and Interruption	EN/IEC 61000-4-29 ⁸	
Electromagnetic Emissions	AS/NZS CISPR 32, class A CISPR 11, group 1, class A CISPR 32, class A EN 55032, class A EN 61000-6-4, class A FCC 47 CFR Part 15, subpart B, class A ICES 003 class A VCCI class A	
Industry		
Marine	DNV ⁸	-
Measurement, control and laboratory use	EN/IEC 61326-1	-
PROFINET IO	PI conformance class B (CC-B) ⁸ IEC 61158-1, IEC 61158-5-10, IEC 61158-6-10 (fieldbus type 10) IEC 61784-1, IEC 61784-2 (communication profile CPF 3)	
Programmable controller	EN/IEC 61131-2	-
Railway applications	EN 50121-4 (S/T apparatus)	
Traffic controller assemblies	NEMA TS 2	
Environmental		
Freefall	IEC60068-2-31, class T2.3	
Shock	IEC60068-2-27 operational: 20g, 11ms, half-sine (DIN rail mount) 45g, 11ms, half-sine (wall mount) non-operational: 65g, 11ms, half-sine	
Vibration	IEC60068-2-6 operational: 2g @10~500Hz non-operational: 2g	

⁵ Refer to the Installation Guide for more details on the safety approved power ratings and thermal conditions.

⁶ Dry heat endurance test performed for seven days at 85°C (185°F).

⁷ Test was applied using the power supply AT-IE048-480-20.

⁸ Certification/test in progress.

Physical Specifications

PRODUCT	WIDTH X DEPTH X HEIGHT	WEIGHT	ENCLOSURE	MOUNTING	PROTECTION RATE
IE340-12GP	91 x 139 x 153 mm (3.58 x 5.47 x 6.02 in)	DIN rail: 2.34 kg (5.16 lbs) Wall mount: 2.23 kg (4.91 lbs)	Aluminium/Sheet Metal shell	DIN rail, wall mount	IP30
IE340-12GT					
IE340-20GP					
IE340L-18GP					

Power Characteristics

PRODUCT	INPUT VOLTAGE ⁹	COOLING	NO POE LOAD			FULL POE LOAD ¹⁰		
			MAX POWER CONSUMPTION	MAX HEAT DISSIPATION	NOISE	MAX POWER CONSUMPTION	MAX HEAT DISSIPATION	NOISE
IE340-12GP	18~57V DC	fanless	24W	81.9 BTU/hr	-	271W	105.8 BTU/hr	-
IE340-12GT						-	-	-
IE340-20GP						271W	105.8 BTU/hr	-
IE340L-18GP	46~57V DC	fanless	24W	81.9 BTU/hr	-	271W	105.8 BTU/hr	-

⁹ PoE sourcing equipment require:
48Vdc to enable IEEE802.3at Type 1 (PoE)
54Vdc to enable IEEE802.3at Type 2 (PoE+)

¹⁰ The Max Power consumption at full PoE load includes the powered device's consumption and margin. The cooling requirements of the switch are smaller than the power draw, because most of the load is dissipated at the PoE powered device and along the cabling. Use these wattage and BTU ratings for facility capacity planning.

Power over Ethernet Sourcing Characteristics

PRODUCT	ENABLED POE PORTS		MAX POE POWER BUDGET ¹¹	MAX POE SOURCING PORTS	
	POE	POE+		POE (15W)	POE+ (30W)
IE340-12GP	8	8	240W	8	8
IE340-12GT	-	-	-	-	-
IE340-20GP	16	16	240W	16	8
IE340L-18GP	16	16	240W	16	8

¹¹ The PoE power budget is shared among all ports; we recommend to configure the dynamic PoE power allocation to optimize the power distribution.

Standards and Protocols

RFC 5492 Capabilities Advertisement with BGP-4
RFC 5925 The TCP Authentication Option
RFC 6793 BGP Support for Four-Octet Autonomous System (AS) Number Space
RFC 7606 Revised Error Handling for BGP UPDATE Messages

RFC 1035 DNS client
RFC 1042 Standard for the transmission of IP datagrams over IEEE 802 networks
RFC 1071 Computing the Internet checksum
RFC 1122 Internet host requirements
RFC 1191 Path MTU discovery
RFC 1256 ICMP router discovery messages
RFC 1518 An architecture for IP address allocation with CIDR
RFC 1519 Classless Inter-Domain Routing (CIDR)
RFC 1542 Clarifications and extensions for Bootstrap
RFC 1591 Domain Name System (DNS)
RFC 1812 Requirements for IPv4 routers
RFC 1918 IP addressing
RFC 2581 TCP congestion control

AlliedWare Plus Operating System

Version 5.5.4

Authentication

RFC 1321 MD5 Message-Digest algorithm
RFC 1828 IP authentication using keyed MD5

Automation and Control

Modbus/TCP
IEC 61158 Industrial communication networks - Fieldbus specifications - PROFINET
IEC 61784 Industrial communication networks - communication profile - PROFINET
IEEE 1588-2019 Precision Clock Synchronization Protocol

Border Gateway Protocol (BGP)

BGP dynamic capability
BGP outbound route filtering
RFC 1772 Application of the Border Gateway Protocol (BGP) in the Internet
RFC 1997 BGP communities attribute
RFC 2439 BGP route flap damping
RFC 2545 Use of BGP-4 multiprotocol extensions for IPv6 inter-domain routing
RFC 2918 Route refresh capability for BGP-4
RFC 3882 Configuring BGP to block Denial-of-Service (DoS) attacks
RFC 4271 Border Gateway Protocol 4 (BGP-4)
RFC 4360 BGP extended communities
RFC 4456 BGP route reflection - an alternative to full mesh iBGP
RFC 4724 BGP graceful restart
RFC 4760 Multiprotocol Extensions for BGP-4
RFC 5065 Autonomous system confederations for BGP

Encryption (Management Traffic Only)

FIPS 180-1 Secure Hash standard (SHA-1)
FIPS 186 Digital signature standard (RSA)
FIPS 46-3 Data Encryption Standard (DES and 3DES)

Ethernet

IEEE 802.2 Logical Link Control (LLC)
IEEE 802.3 Ethernet
IEEE 802.3ab 1000BASE-T
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.3at Power over Ethernet up to 30W (PoE+)
IEEE 802.3az Energy Efficient Ethernet (EEE)
IEEE 802.3u 100BASE-X
IEEE 802.3x Flow control - full-duplex operation
IEEE 802.3z 1000BASE-X

IPv4 Features

RFC 768 User Datagram Protocol (UDP)
RFC 791 Internet Protocol (IP)
RFC 792 Internet Control Message Protocol (ICMP)
RFC 793 Transmission Control Protocol (TCP)
RFC 826 Address Resolution Protocol (ARP)
RFC 894 Standard for the transmission of IP datagrams over Ethernet networks
RFC 919 Broadcasting Internet datagrams
RFC 922 Broadcasting Internet datagrams in the presence of subnets
RFC 932 Subnetwork addressing scheme
RFC 950 Internet standard subnetting procedure
RFC 951 Bootstrap Protocol (BootP)
RFC 1027 Proxy ARP

IPv6 Features

RFC 1981 Path MTU discovery for IPv6
RFC 2460 IPv6 specification
RFC 2464 Transmission of IPv6 packets over Ethernet networks
RFC 3484 Default address selection for IPv6
RFC 3587 IPv6 global unicast address format
RFC 3596 DNS extensions to support IPv6
RFC 4007 IPv6 scoped address architecture
RFC 4193 Unique local IPv6 unicast addresses
RFC 4213 Transition mechanisms for IPv6 hosts and routers
RFC 4291 IPv6 addressing architecture
RFC 4443 Internet Control Message Protocol (ICMPv6)
RFC 4861 Neighbor discovery for IPv6
RFC 4862 IPv6 Stateless Address Auto-Configuration (SLAAC)
RFC 5014 IPv6 socket API for source address selection
RFC 5095 Deprecation of type 0 routing headers in IPv6
RFC 5175 IPv6 Router Advertisement (RA) flags option
RFC 6105 IPv6 Router Advertisement (RA) guard

Management

AT Enterprise MIB including AMF Plus MIB and traps
 Optical DDM MIB
 SNMPv1, v2c and v3
 ANSI/TIA-1057 Link Layer Discovery Protocol-Media Endpoint Discovery (LLDP-MED)
 IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
 RFC 1155 Structure and identification of management information for TCP/IP-based Internets
 RFC 1157 Simple Network Management Protocol (SNMP)
 RFC 1212 Concise MIB definitions
 RFC 1213 MIB for network management of TCP/IP-based Internets: MIB-II
 RFC 1215 Convention for defining traps for use with the SNMP
 RFC 1227 SNMP MUX protocol and MIB
 RFC 1239 Standard MIB
 RFC 1724 RIPv2 MIB extension
 RFC 2011 SNMPv2 MIB for IP using SMIv2
 RFC 2012 SNMPv2 MIB for TCP using SMIv2
 RFC 2013 SNMPv2 MIB for UDP using SMIv2
 RFC 2578 Structure of Management Information v2 (SMIv2)
 RFC 2579 Textual conventions for SMIv2
 RFC 2580 Conformance statements for SMIv2
 RFC 2674 Definitions of managed objects for bridges with traffic classes, multicast filtering and VLAN extensions
 RFC 2741 Agent extensibility (AgentX) protocol
 RFC 2819 RMON MIB (groups 1,2,3 and 9)
 RFC 2863 Interfaces group MIB
 RFC 3176 sFlow: a method for monitoring traffic in switched and routed networks
 RFC 3411 An architecture for describing SNMP management frameworks
 RFC 3412 Message processing and dispatching for the SNMP
 RFC 3413 SNMP applications
 RFC 3414 User-based Security Model (USM) for SNMPv3
 RFC 3415 View-based Access Control Model (VACM) for SNMP
 RFC 3416 Version 2 of the protocol operations for the SNMP
 RFC 3417 Transport mappings for the SNMP
 RFC 3418 MIB for SNMP
 RFC 3621 Power over Ethernet (PoE) MIB
 RFC 3635 Definitions of managed objects for the Ethernet-like interface types
 RFC 3636 IEEE 802.3 MAU MIB
 RFC 4022 MIB for the Transmission Control Protocol (TCP)
 RFC 4113 MIB for the User Datagram Protocol (UDP)
 RFC 4188 Definitions of managed objects for bridges
 RFC 4292 IP forwarding table MIB
 RFC 4293 MIB for the Internet Protocol (IP)
 RFC 4318 Definitions of managed objects for bridges with RSTP
 RFC 4560 Definitions of managed objects for remote ping, traceroute and lookup operations
 RFC 5424 The Syslog protocol
 RFC 6527 Definitions of managed objects for VRRPv3

Multicast Support

Bootstrap Router (BSR) mechanism for PIM-SM
 IGMP query solicitation
 IGMP snooping (IGMPv1, v2 and v3)
 IGMP snooping fast-leave
 IGMP/MLD multicast forwarding (IGMP/MLD proxy)
 MLD snooping (MLDv1 and v2)
 PIM-SM and SSM for IPv6
 RFC 2236 Internet Group Management Protocol v2 (IGMPv2)

RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 RFC 2715 Interoperability rules for multicast routing protocols
 RFC 3306 Unicast-prefix-based IPv6 multicast addresses
 RFC 3376 IGMPv3
 RFC 3590 Source Address Selection for the Multicast Listener Discovery (MLD) Protocol
 RFC 3810 Multicast Listener Discovery v2 (MLDv2) for IPv6
 RFC 3956 Embedding the Rendezvous Point (RP) address in an IPv6 multicast address
 RFC 3973 PIM Dense Mode (DM)
 RFC 4541 IGMP and MLD snooping switches
 RFC 4604 Using IGMPv3 and MLDv2 for source-specific multicast
 RFC 4607 Source-specific multicast for IP
 RFC 7761 Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol specification

Open Shortest Path First (OSPF)

OSPF link-local signaling
 OSPF MD5 authentication
 OSPF restart signaling
 Out-of-band LSDB resync
 RFC 1245 OSPF protocol analysis
 RFC 1246 Experience with the OSPF protocol
 RFC 1370 Applicability statement for OSPF
 RFC 1765 OSPF database overflow
 RFC 2328 OSPFv2
 RFC 2370 OSPF opaque LSA option
 RFC 2740 OSPFv3 for IPv6
 RFC 3101 OSPF Not-So-Stubby Area (NSSA) option
 RFC 3509 Alternative implementations of OSPF area border routers
 RFC 3623 Graceful OSPF restart
 RFC 3630 Traffic engineering extensions to OSPF
 RFC 4552 Authentication/confidentiality for OSPFv3
 RFC 5329 Traffic engineering extensions to OSPFv3
 RFC 5340 OSPFv3 for IPv6 (partial support)

Quality of Service (QoS)

IEEE 802.1p Priority tagging
 RFC 2211 Specification of the controlled-load network element service
 RFC 2474 DiffServ precedence for eight queues/port
 RFC 2475 DiffServ architecture
 RFC 2597 DiffServ Assured Forwarding (AF)
 RFC 2697 A single-rate three-color marker
 RFC 2698 A two-rate three-color marker
 RFC 3246 DiffServ Expedited Forwarding (EF)

Resiliency Features

IEC 62439-2 Media Redundancy Protocol (MRP)
 IEEE 802.3ad Static and dynamic link aggregation
 IEEE 802.1ag CFM Continuity Check Protocol (CCP)
 IEEE 802.1AX Link aggregation (static and LACP)
 IEEE 802.1D MAC bridges
 IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
 IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 ITU-T G.8032 / Y.1344 Ethernet Ring Protection Switching (ERPS)
 RFC 5798 Virtual Router Redundancy Protocol version 3 (VRRPv3) for IPv4 and IPv6

Routing Information Protocol (RIP)

RFC 1058 Routing Information Protocol (RIP)
 RFC 2080 RIPng for IPv6
 RFC 2081 RIPng protocol applicability statement
 RFC 2082 RIP-2 MD5 authentication
 RFC 2453 RIPv2

Security Features

SSH remote login
 SSLv2 and SSLv3
 TACACS+ Accounting, Authentication, Authorization (AAA)
 IEEE 802.1X Authentication protocols (TLS, TTLS, PEAP and MD5)
 IEEE 802.1X Multi-suplicant authentication
 IEEE 802.1X Port-based network access control
 RFC 2818 HTTP over TLS ("HTTPS")
 RFC 2865 RADIUS authentication
 RFC 2866 RADIUS accounting
 RFC 2868 RADIUS attributes for tunnel protocol support
 RFC 2986 PKCS #10: certification request syntax specification v1.7
 RFC 3579 RADIUS support for Extensible Authentication Protocol (EAP)
 RFC 3580 IEEE 802.1x RADIUS usage guidelines
 RFC 3748 Extensible Authentication Protocol (EAP)
 RFC 4251 Secure Shell (SSHv2) protocol architecture
 RFC 4252 Secure Shell (SSHv2) authentication protocol
 RFC 4253 Secure Shell (SSHv2) transport layer protocol
 RFC 4254 Secure Shell (SSHv2) connection protocol
 RFC 5176 RADIUS CoA (Change of Authorization)
 RFC 5246 Transport Layer Security (TLS) v1.2
 RFC 5280 X.509 certificate and Certificate Revocation List (CRL) profile
 RFC 5425 Transport Layer Security (TLS) transport mapping for Syslog
 RFC 5656 Elliptic curve algorithm integration for SSH
 RFC 6125 Domain-based application service identity within PKI using X.509 certificates with TLS
 RFC 6614 Transport Layer Security (TLS) encryption for RADIUS
 RFC 6668 SHA-2 data integrity verification for SSH

Services

RFC 854 Telnet protocol specification
 RFC 855 Telnet option specifications
 RFC 857 Telnet echo option
 RFC 858 Telnet suppress go ahead option
 RFC 1091 Telnet terminal-type option
 RFC 1350 The TFTP protocol (revision 2)
 RFC 1985 SMTP service extension
 RFC 2049 MIME
 RFC 2131 DHCPv4 (server, relay and client)
 RFC 2132 DHCP options and BootP vendor extensions
 RFC 2616 Hypertext Transfer Protocol - HTTP/1.1
 RFC 2821 Simple Mail Transfer Protocol (SMTP)
 RFC 2822 Internet message format
 RFC 3046 DHCP relay agent information option (DHCP option 82)
 RFC 3315 Dynamic Host Configuration Protocol for IPv6 (DHCPv6)
 RFC 3396 Encoding Long Options in the Dynamic Host Configuration Protocol (DHCPv4)
 RFC 3633 IPv6 prefix options for DHCPv6
 RFC 3646 DNS configuration options for DHCPv6
 RFC 3993 Subscriber-ID suboption for DHCP relay agent option
 RFC 4954 SMTP Service Extension for Authentication
 RFC 5905 Network Time Protocol (NTP) version 4

VLAN LAN Features

Generic VLAN Registration Protocol (GVRP)
 Voice VLAN
 IEEE 802.1ad Provider bridges (VLAN stacking, Q-in-Q)
 IEEE 802.1Q Virtual LAN (VLAN) bridges
 IEEE 802.1v VLAN classification by protocol and port
 IEEE 802.3ac VLAN tagging

IE340 Series | Industrial Ethernet Layer 3 Switches

Premium Licenses

From AW+ 5.5.4-0 onward, the equipment provides all baseline capabilities, except those features enabled by the Premium License.

NAME	DESCRIPTION	INCLUDES
AT-IE340-FL01	IE340 Series Premium license	<ul style="list-style-type: none"> ▶ BGP (64 routes) ▶ BGP+ (64 routes) ▶ OSPF (64 routes) ▶ OSPFv3 (64 routes) ▶ PIM-SM, DM and SSM (256 routes) ▶ PIMv6-SM and SSM (256 routes) ▶ RIP (64 routes) ▶ RIPng (64 routes)

Ordering Information

Switches

The DIN rail and wall mount kits are included.
The management serial console cable is NOT included.

AT-IE340-12GP-xx

8x 10/100/1000T, 4x 100/1000X SFP,
Industrial Ethernet, Layer 3 Switch, PoE+ Support

AT-IE340-12GT-xx

8x 10/100/1000T, 4x 100/1000X SFP,
Industrial Ethernet, Layer 3 Switch

AT-IE340-20GP-xx

16x 10/100/1000T, 4x 100/1000X SFP,
Industrial Ethernet, Layer 3 Switch, PoE+ Support

AT-IE340L-18GP-80

16x 10/100/1000T, 2x 1000X SFP,
Industrial Ethernet, Layer 3 Switch, PoE+ Support

Where xx = 80 standard Country of Origin
980 TAA compliant Country of Origin

Power Supplies

AT-DRB50-48-1

50W @48Vdc, Industrial AC/DC power supply,
DIN rail mount

AT-IE048-240-20

240W @48Vdc, Industrial AC/DC power supply,
DIN rail mount (5 years warranty)

AT-IE048-480-20

480W @48Vdc, Industrial AC/DC power supply,
DIN rail mount (5 years warranty)

AT-SDR120-48

120W @48Vdc, Industrial AC/DC power supply,
DIN rail mount

AT-SDR240-48

240W @48Vdc, Industrial AC/DC power supply,
DIN rail mount

AT-SDR480-48

480W @48Vdc, Industrial AC/DC power supply,
DIN rail mount

Supported SFP Modules

Refer to the installation guide for the recommended Max.
Operating Temperature according to the selected SFP
module.

1000Mbps SFP Modules

AT-SPBD10-13

10 km, 1G BiDi SFP, LC, SMF, I-Temp,
(1310 Tx/1490 Rx)

AT-SPBD10-14

10 km, 1G BiDi SFP, LC, SMF, I-Temp,
(1490 Tx/1310 Rx)

AT-SPBD20-13/I

20 km, 1G BiDi SFP, SC, SMF, I-Temp,
(1310 Tx/1490 Rx)

AT-SPBD20-14/I

20 km, 1G BiDi SFP, SC, SMF, I-Temp,
(1490 Tx/1310 Rx)

AT-SPBD20LC/I-13

20 km, 1G BiDi SFP, LC, SMF, I-Temp, TAA
(1310 Tx/1490 Rx)

AT-SPBD20LC/I-14

20 km, 1G BiDi SFP, LC, SMF, I-Temp, TAA
(1490 Tx/1310 Rx)

AT-SPBD40-13/I

40 km, 1G BiDi SFP, LC, SMF, I-Temp,
(1310 Tx/1490 Rx)

AT-SPBD40-14/I

40 km, 1G BiDi SFP, LC, SMF, I-Temp,
(1490 Tx/ 1310 Rx)

AT-SPEX/E-90

2 km, 1000EX SFP, LC, MMF, 1310 nm, Ext. Temp,
TAA

AT-SPLX10a

10 km, 1000LX SFP, LC, SMF, 1310 nm, TAA

AT-SPLX10/I

10 km, 1000LX SFP, LC, SMF, 1310 nm, I-Temp

AT-SPLX10/E-90

10 km, 1000LX SFP, LC, SMF, 1310 nm, Ext. Temp,
TAA

AT-SPLX40

40 km, 1000LX SFP, LC, SMF, 1310 nm

AT-SPLX40/E-90

40 km, 1000LX SFP, LC, SMF, 1310 nm, Ext. Temp,
TAA

AT-SPSX-90

550 m, 1000SX SFP, LC, MMF, 850 nm, TAA

AT-SPSX/I-90

550 m, 1000SX SFP, LC, MMF, 850 nm, I-Temp,
TAA

AT-SPSX/E-90

550 m, 1000SX SFP, LC, MMF, 850 nm, Ext. Temp,
TAA

AT-SPTX-90

100 m, 10/100/1000T SFP, RJ-45, TAA

AT-SPTX/I

100 m, 10/100/1000T SFP, RJ-45, I-Temp

AT-SPZX120/I

120 km, 1000LX SFP, LC, SMF, 1550 nm, I-Temp,
TAA

100Mbps SFP modules¹²

AT-SPFX/2-90

2 km, 100FX SFP, LC, MMF, 1310 nm, TAA

AT-SPFX30/I-90

30 km, 100FX SFP, LC, SMF, 1310 nm, I-Temp, TAA

Accessories

AT-VT-Kit3

Management cable (USB to serial console)

¹² IE340L model does not support this feature.