

TQm5403

3-radio 802.11ac Wave 2 Wireless Access Point

The Allied Telesis Enterprise-class TQm5403 Wireless Access Point features IEEE 802.11ac Wave 2 technology with two spatial streams to deliver a raw capacity of 2.133 Gigabits.



Overview

The Allied Telesis TQm5403 is a three-radio wireless LAN access point that supports IEEE802.11ac Wave 2, and is ideal for small to medium enterprise networks, providing a high-value and easily deployed wireless solution.

The TQm5403 has a single 2.4GHz radio and dual 5GHz IEEE 802.11ac radios, and supports Multi-User Multiple Input and Multiple Output (MU-MIMO), allowing multiple clients to send and receive data at the same time, substantially increasing throughput. Combined with a comprehensive feature-set, the APs provide superior wireless connectivity.

The TQm5403 can operate in standalone mode, using its intuitive web-based user interface. For medium scale installations it can be managed by Allied Telesis Autonomous Wave Control (AWC). With AWC, the wireless network is regularly analyzed, and APs are dynamically updated to reduce interference, minimize coverage gaps, and optimize performance—all with no user intervention. The Allied Telesis network management platform, Vista Manager EX, has an AWC wireless management plugin that supports up to 100 APs.

Flexible deployment options enable easy installation, with the TQm5403 able to be used on the desktop or mounted on a wall or ceiling. Power may be supplied by Power over Ethernet, for the simplicity of having the Ethernet network connect and power the APs, or by an optional AC power adapter.

Key Features

IEEE 802.11ac Wave 2

- ▶ IEEE 802.11ac Wave 2 wireless connectivity delivers Gigabit performance and throughput. In crowded wireless environments, efficient bandwidth distribution is important. Wave 2 uses Multi-user MIMO technology to simultaneously communicate with multiple clients at once, reducing contention and improving throughput by up to three times.
- ▶ Multi-user MIMO uses beamforming, where the AP focuses wireless signal towards connected devices, rather than simply radiating the signal evenly. This improves range and speed for each user, and reduces interference.

Tri-radio, with Band Steering

- ▶ The TQm5403 contains three IEEE 802.11 2ss radios to enable concurrent Wi-Fi communications: one at 2.4GHz band, and two at 5GHz band. This alleviates network congestion and isolates any legacy client devices affecting performance.
- ▶ Band steering prompts newly connecting devices to use a band with little current congestion to distribute wireless traffic, provide maximum throughput, and the best user experience.

Virtual APs with Multiple SSIDs

- ▶ The TQm5403 supports Virtual AP (VAP) functionality, with the assignment of different SSIDs and security policies for each VAP on the physical device.
- ▶ VAPs can be mapped to VLANs for logical network separation and improved throughput. Enable communication by application, function or users.

IEEE 802.11e Wireless Multimedia (WMM)

- ▶ Quality of Service (QoS) optimizes the performance of voice, video, and data applications, as each has different latency, bandwidth and performance requirements. QoS traffic prioritization ensures the timely delivery of these services.

IEEE 802.11i (security)

- ▶ This feature set facilitates strong encryption, authentication and key management strategies, guaranteeing data and system security. In addition to Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP), IEEE 802.1X key distribution via RADIUS controls access to the network.

Link Aggregation

- ▶ The TQm5403 features two 10/100/1000T Ethernet ports. These can be combined into a single virtual connection using static link aggregation, to double the bandwidth from the AP to the wired network.

Cascade Mode

- ▶ Adding deployment flexibility, one of the Ethernet ports may be used in cascade mode to connect an additional wired network device. This may be an end device such as a PC or printer, or a networking device, such as a switch or router.

Captive Portal

- ▶ Manage user access to the Wi-Fi network with captive portal. New users are taken to a login page to authenticate before gaining access to any online resources and applications.
- ▶ Login options include direct online access, external authentication, or redirection to third party services—for example social media sites like Facebook or Twitter.

Dynamic VLANs

- ▶ Dynamic VLANs simplify management by enabling users to be separated on different VLANs according to rules defined in a centralized user database. When a user connects, their credentials are checked and the VLAN assigned automatically to the AP. An external RADIUS server is supported and a secondary RADIUS server can also be specified for redundancy.

Airtime Fairness

- ▶ Airtime Fairness equally assigns airtime to each connected client, to ensure fair and predictable sharing of bandwidth. This feature prevents any client from monopolizing the bandwidth when transferring a large amount of data, and ensures consistent performance for all users.

Fast Roaming

- ▶ Fast roaming 802.11k, 802.11v, and 802.11r optimize discovering and selecting the best available AP in a Wi-Fi network. It establishes rapid connectivity for users to seamlessly move between APs, as the APs exchange security keys, so the client device does not need to re-authenticate on the RADIUS server as they roam.

Passpoint® support

- ▶ Wi-Fi Alliance certified Passpoint enables auto-detection and connection of client devices, removing the need for users to find and authenticate on wireless networks.

Specifications

Physical Specifications

PRODUCT	WIDTH X DEPTH X HEIGHT	WEIGHT	10/100/1000T (RJ-45) COPPER PORTS
TQm5403	215 x 215 x 48 mm (8.46 x 8.46 x 1.89 in)	700 g (24.69 oz)	2 (1 PoE-in port)

Power Characteristics

PRODUCT	POWER SUPPLY	POWER CONSUMPTION		MAX HEAT DISSIPATION
		AVERAGE	MAXIMUM	
TQm5403	100-240VAC	10W	20W	67 BTU/h
	POE	10W	19W	64 BTU/h

Wireless

- ▶ Multi-channel operation
- ▶ Airtime fairness
- ▶ Automatic channel selection
- ▶ Automatic control of transmission power
- ▶ Band Steering
- ▶ Fast roaming
- ▶ RF load balancing
- ▶ Wireless Distribution System (WDS)
- ▶ Wi-Fi Multimedia (WMM) for traffic prioritization

Operational Modes

- ▶ Centrally managed in multi-channel mode by Vista Manager EX (up to 100 APs)¹
- ▶ Standalone¹

Management

- ▶ Graphical User Interface (HTTP/HTTPS)
- ▶ Simple Network Management Protocol (SNMPv1, v2c, v3)
- ▶ Firmware upgrade
- ▶ Backup/restore settings
- ▶ Syslog notification
- ▶ DHCP client
- ▶ NTP client

Security

- ▶ Authentication and accounting
 - IEEE 802.1X authentication and accounting
 - IEEE 802.1X RADIUS support
 - Shared Key Authentication
 - WPA (Enterprise, Personal)
 - WPA2 (Enterprise, Personal)
 - WPA3 (Enterprise): GCMP (AES)
 - WPA3 (Personal): CCMP (AES)
 - Captive Portal ((External RADIUS, Click-Through, Authentication Page Redirection, Virtual IP Address, RADIUS Accounting, Walled Garden) Passpoint²)
- ▶ Encryption
 - WEP: 64/128 bit (IEEE 802.11a/b/g only)
 - WPA/WPA2: CCMP (AES), TKIP
 - WPA3 (Enterprise): GCMP (AES)
 - WPA3 (Personal) : CCMP (AES)
- ▶ MAC address filtering (Up to 2048 MAC address)
- ▶ SSID hiding/ignoring
- ▶ Client isolation
- ▶ Neighbor AP detection

Compliance

- Certificates
- ▶ FCC
 - ▶ CE
 - ▶ RCM
 - ▶ Wi-Fi certified (ID:WFA75927)
 - ▶ IMDA (For Singapore)
 - ▶ KC (For South Korea)
 - ▶ MIC (For Vietnam)
 - ▶ NBTC (For Thailand)
 - ▶ BSMI/NCC (For Taiwan)
 - ▶ OFCA (For Hong Kong)
 - ▶ SIRIM (For Malaysia)
 - ▶ WPC (For India)
 - ▶ IC (For Canada)

Safety

- ▶ EN 60950-1
 - ▶ EN 62368-1
 - ▶ UL 60950-1
 - ▶ UL 62368-1
- ElectroMagnetic Compatibility
- ▶ AS/NZS 2772.2
 - ▶ EN 301 489-1
 - ▶ EN 301 489-17
 - ▶ EN 55024
 - ▶ EN 55032, Class B
 - ▶ EN 60601-1-2:2015 (For Medical)
 - ▶ EN 61000-3-2, Class A
 - ▶ EN 61000-3-3
 - ▶ EN 61000-4-2
 - ▶ EN 61000-4-3
 - ▶ EN 61000-4-4
 - ▶ EN 61000-4-5
 - ▶ EN 61000-4-6
 - ▶ EN 61000-4-8
 - ▶ EN 61000-4-11
 - ▶ FCC 47 CFR Part 15, Subpart B
 - ▶ VCCI, class B

Radio equipment

- ▶ AS/NZS 4268
- ▶ EN 300 328
- ▶ EN 301 893
- ▶ FCC 47 CFR Part 15, Subpart C
- ▶ FCC 47 CFR Part 15, Subpart E³
- ▶ FCC part 2

Environmental Specifications

- ▶ Operating temperature range:
 - PoE: 0°C to 50°C (32°F to 122°F)
 - AC adapter: 0°C to 45°C (32°F to 113°F)
- ▶ Storage temperature range:
 - 25°C to 70°C (-13°F to 158°F)
- ▶ Operating relative humidity range:
 - 90% non-condensing
- ▶ Storage relative humidity range:
 - 95% non-condensing

Embedded Antennas⁴

- Omni-directional
- ▶ Frequency band: 2.4 GHz
 - ▶ Max. peak gain: 3.95dBi⁵
- Omni-directional
- ▶ Frequency band: 5GHz (5.2-5.3GHz)
 - ▶ Max. peak gain: 4.20dBi⁵
- Omni-directional
- ▶ Frequency band: 5GHz (5.6-5.8GHz)
 - ▶ Max. peak gain: 4.83dBi⁵

Radio Characteristics

- Supported frequencies:
- ▶ 2.400 ~ 2.4835 GHz
 - ▶ 5.150 ~ 5.250 GHz
 - ▶ 5.250 ~ 5.350 GHz
 - ▶ 5.470 ~ 5.725 GHz
 - ▶ 5.725 ~ 5.850 GHz
- Modulation Technique
- ▶ 802.11a/g/n/ac: OFDM
 - ▶ 802.11b: DSSS, CCK, DQPSK, DBPSK
 - ▶ 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
 - ▶ 802.11a/g/n: BPSK, QPSK, 16QAM, 64QAM, 256QAM
- Data Rate⁵
- ▶ 802.11a/g:
 - 54/48/36/24/18/12/9/6Mbps
 - ▶ 802.11b: 11/5.5/2/1Mbps
 - ▶ 802.11n: 6.5 - 400Mbps⁶ (MCS 0 - 15)
 - ▶ 802.11n: 6.5 - 300Mbps (MCS 0 - 15)
 - ▶ 802.11ac: 6.5 - 866.7Mbps (MCS 0 - 9, NSS 1 - 2)

Media Access

- ▶ CSMA/CA + Ack with RTS/CTS

Diversity

- ▶ Spatial diversity

¹ In standalone mode, supports up to 127 clients per radio

² Wi-Fi Alliance certified Passpoint

³ Supported frequencies: 5.150 ~ 5.250 GHz
5.725 ~ 5.850 GHz

⁴ Radiation Pattern of Antenna is in the Installation Guide

⁵ Values listed for gain and data rate are maximums, and the actual values will vary depending on use.

⁶ Using 256 Quadrature Amplitude Modulation

Wireless Management Licenses

Wireless management of the TQm5403 is available from the Vista Manager EX network management platform, and from Vista Manager mini running on our SwitchBlade x908 GEN2, x950, x930, x550, x530 Series switches or AR4050S UTM firewall.

PLATFORM	LICENSE NAME	DESCRIPTION	MAX SUPPORTED APs
Vista Manager EX	AT-FL-VISTA-BASE-1/5YR	Vista Manager EX network monitoring and management software license	NA
Vista Manager EX (Windows)	AT-FL-VISTA-AWC10-1/5YR ⁷	Vista Manager AWC plug-in license for managing up to 10 access points	100
Vista Manager EX (Virtual (VRT))	AT-FL-VISTA-AWC10-1/5YR ⁷	Vista Manager AWC plug-in license for managing up to 10 access points	100
Vista Manager EX (Network Appliance)	AT-FL-VISTA-AWC10-1/5YR ⁷	Vista Manager AWC plug-in license for managing up to 10 access points	100
SwitchBlade x908 GEN2	AT-SW-AWC10-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 10 access points	100
x950 Series	AT-SW-AWC10-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 10 access points	100
x930 Series	AT-SW-AWC10-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 10 access points	100
x550 Series	AT-SW-AWC10-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 10 access points	45
x530 Series	AT-SW-AWC10-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 10 access points	45
AR4050S UTM Firewall	AT-RT-AWC5-1/5YR ⁸	Cumulative Autonomous Wave Controller (AWC) license for up to 5 access points	25

⁷ The AWC plug-in requires an AWC license, and a Vista Manager EX base license to operate on Vista Manager EX
⁸ 5 APs can be managed for free. Purchase one license per 10 additional APs on switches, or one license per 5 additional APs on the AR4050S Firewall

Standards

Ethernet

- IEEE 802.1AX-2008 Link Aggregation (static)
- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3x Flow Control
- IEEE 802.3at Power over Ethernet+
- IEEE 802.1Q VLAN Tagging

Wireless

- IEEE 802.11 a/b/g/n/ac (Wave 2) 2x2:2ss MU-MIMO
- IEEE 802.11d Regulatory Domain
- IEEE 802.11h DFS/TPC
- IEEE 802.11k Radio Resource Measurement of Wireless LANs
- IEEE 802.11v Basic Service Set Transition Management Frames
- IEEE 802.11r Fast Basic Service Set Transition
- IEEE 802.11e WMM for Quality of Service
- IEEE 802.11i WPA/WPA2/WPA3 802.1x for Security

Ordering Information

AT-TQm5403-xx
 SMB 802.11ac Wave 2 Wireless Access Point with 3 radios and embedded antenna

- Where xx =
- 01 Regulatory Domain: United States Reserved
 - 02 Regulatory Domain: Taiwan
 - 03 Regulatory Domain: Canada
 - 00 Regulatory Domain: Other countries^{9, 10}

⁹ Please check the Compliance section on page 2 to see which countries are certified to use this access point.
¹⁰ To order this access point for use in Japan, please see the Japanese datasheet.

Related Products

- AT-MWS0091**
AC adapter
 - AT-6101GP-yy**
Gigabit Ethernet PoE+ (802.3at) injector
 - AT-7101GHTm-yy**
Multi-Gigabit Ethernet PoE++ (802.3bt) injector
 - AT-BRKT-CONV-AP1**
Replacement bracket converter for the TQm5403 AP
- Where yy = 10 for US power cord
 30 for UK power cord
 40 for Australian power cord
 50 for European power cord